



Type

Pressure booster systems

Model	XKJ-601IA	XKJ-801IA	XKJ-901IA	XKJ-1101IA	XKJ-1301IA
Supply Power	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
Input Power	600W	800W	900W	1100W	1300W
Max. Head	35m	40m	42m	45m	46m
Max. Flow	3.6m ³ /h	3.6m ³ /h	3.6m ³ /h	4.6m ³ /h	5.0m ³ /h
Max. Suct	8m	8m	8m	8m	8m
Max. Dia. of Particle	3mm	3mm	3mm	3mm	3mm
Outlet/Inlet	1"X1"	1"X1"	1"X1"	1"X1"	1"X1"
Cable	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m	H07RN-F 1.5m
Tank	20L	20L	20L	20L	20L
Opening Pressure	1.4bar	1.4bar	1.4bar	1.4bar	1.8bar
Shutoff Pressure	2.4bar	2.8bar	2.8bar	2.8bar	3.2bar
Operating Limits	Fluid temperature up to 35°C; Ambient temperature up to 40°C.				